## **UPS UNINTERRUPTABLE POWER SUPPLY**

## Characteristic

- 1.Double way output
- 2. Four pointer meter display output voltage and current value respectively
- 3. Under steady voltage and current condition, the voltage and current can be changed automatically, and its can be indicated by luminous pipe.
- 4. Using limied current protection way, limited current point may optionally adjust
- 5. Double way output voltage may use in series and parallel connection
- 6.Au is plastic plate, the exterior is exquisite and applied

## Technical Index

Туре		Output Volatge	Output Current
DSJ-1515		0-15V	0-15A
DSJ-1520	0	0-15V	0-20A
DSJ-3010		0-30V	0-10A
DSJ-3015		0-30V	0-15A
DSJ-605		0-60V	0-5A

Waves and voice: CV≤3mvrms CC≤10mAms

Power supply domino effect:  $CV \le 2 \times 10^{-4} + 3 \text{mv } CC \le 5 \times 10^{-3} + 3 \text{mA}$ 

Load domino effect:CV≤2×10<sup>-4</sup>+10mv CC≤5×10<sup>-3</sup>+10mA

Dimension and weight: 390×155×133



- 1. Double way output
- 2. Four digital led display output voltage and current value respectively
- 3. Under steady voltage and current condition. the voltage and current can be changed automatically, its can be indicated by luminous pipe.
- 4. Using limied current protection way. Limited current point may adjust optionally
- 5. Double way output voltage may use in series and parallel connection
- 6.All are plastic plate, the exterior is exquisite and applied

## **Technical Index**


Туре	Output Volatge	Output Current
DSJ-1515	0-15V	0-15A
DSJ-1520	0-15V	0-20A
DSJ-3010	0-30V	0-10A
DSJ-3015	0-30V	0-15A
DSJ-605	0-60V	0-5A



Power supply domino effect:  $CV \le 2 \times 10^{-4} + 3 \text{mv } CC \le 5 \times 10^{-3} + 3 \text{mA}$ 

Load domino effect:CV≤2×10<sup>-4</sup>+10mv CC≤5×10<sup>-3</sup>+10mA

Dimension and weight:390×155×133





DC regulated power supply series digital type