

# Cable Tracer and Test-Phone Generator



## 183 CB

### Cable Tracer

- Trace wires or cables.
- Volume control.
- Tip & Ring identification.
- 2 bi-colored LEDs ( Line 1 & Line 2).
- Tone speed selection : Fast & Slow.
- A phone jack is designed for headset or handset.  
(Amplifier probe)

### Phone Tester

- Continuity and resistance testing for voltage-free objects.
- Check direct and alternating voltages.
- Testing capacitors.
- Testing diodes.
- Power ON/OFF switch.
- The indication of the LED lamp and the sound of the buzzer can occur at the same time.
- The LED indication for Power ON status.



### SPECIFICATIONS

#### Amplifier Probe

Frequency	1Hz~12kHz
Receiver distance	<50cm
Sensitivity control	√
Probe tip	Fixed
Power source	9V(6F22) × 1
Dimensions	230(L) × 56(W) × 27(D)mm
Weight (battery included)	Approx. 125g

#### Tone Generator

Wave form	Square Wave
Frequency	1kHz±15%
Over voltage protection	80V DC
Single tone	—
Alternating tone	Fast and Slow
Connection	RJ11 connector, alligator clip x 2
Power source	1.5V (AA) × 6
Dimensions	143(L) × 74.5(W) × 33.6(D)mm
Weight (battery included)	Approx. 318g

#### Phone Tester

Loud speaker	√
Continuity testing	√
Checking resistance	√
ACV/DCV checking	√
Checking capacitors	√
Checking diodes	√

#### General

Operating temp & humidity	0°~40° C, 80% Max.
Storage temp & humidity	-10°~50° C, 80% Max.
Safety standard	EN 61326-1 EN 55011 EN 61000-4-2 EN 61000-4-3
Accessories	Instruction manual Test leads Carry case Batteries