

KC-65

Detail

Height : 340 mm

Weight : 3.5 kgs

Specifications:

Drive unit : 14.4V DC motor

Charger (BOCSH):

Input voltage : KC-65-120

110V single phase AC

Input voltage : KC-65-230

230V single phase AC

Input frequency : 50~60 Hz

Input current : 21.75 VA

Cutting Capacity:

Max cable diameter:

Nonferrous 65 mm

Accessories:

KuDos plastic carrying case

14.4V Battery, 110V or 230V Charger



※For reference only


Model no.	Specification
	600V-CV325 mm ² ; (31 mm OD)
Polyethylene cable	600V-CV150 mm ² ; x3 (46 mm OD)
	600V-CV500 mm ² ; (38 mm OD)
	6KV-CVT500 mm ² ; (45 mm OD)
Multi-core vinyl insulation cable	VVR150 mm ² ; (47 mm OD) 3 core
Soft copper cable	IV500mm ² ; (35 mm OD)
Hard copper cable	150mm ² ; (21 mm OD)

■ Close View of NEW KC series Features

- Gear rotated blade design.

BRUSH DESIGN

- It can anti-dust & prevent impurities in the machine.



SWITCH

- Forward → Neutral → Backward

SAFETY SWITCH DESIGN


- Prevent missed operate the tool, It request to press both safety switch & switch to operate the tool.

- Ergonomic design and comfortable to use with anti-slip coated grip.

SWITCH



- Bosch battery power indicator 14.4V Li-ion battery.



OVERLOAD INDICATOR

- When red light flashed, It shows the battery was overloaded. When out of battery, The red light will light on.

