

**NEW  
PRODUCT**

# BATTERY OPERATED TOOLS

## ■ Model No. **KCV-50** (with Li-ion Battery & Charger)

Height : 317 mm  
Weight : 2.2 kgs (w/o battery)

## ■ Cutting Capacity:

- Max. Cable diameter:  
Nonferrous 50 mm

## ■ Specifications:

Drive unit: 18V DC Motor  
Charger (BOCSH):  
Input voltage : **KCV-50-120**  
110V Single Phase AC  
Input voltage : **KCV-50-230**  
230V Single Phase AC  
Input frequency: 50-60 Hz  
Input current: 21.75 VA

## ■ Accessories:

- KuDos plastic carrying case
- 18V Battery, 110V or 230V Charger  
(See page 69)



For reference only

Model No.	Specification
Polyethylene cable	600V-CV325 mm <sup>2</sup> (31 mm OD)
	600V-CV150 mm <sup>2</sup> x 3(46 mm OD)
	600V-CV500 mm <sup>2</sup> (38 mm OD)
	6KV-CVT500 mm <sup>2</sup> (45 mm OD)
Multi-core vinyl insulation cable	VVR150 mm <sup>2</sup> (47 mm OD) 3 core
Soft copper cable	IV500 mm <sup>2</sup> (35 mm OD)
Hard copper cable	150 mm <sup>2</sup> (21 mm OD)

## ■ Close View of NEW KCV series Features:

