

● DESCRIPTION

NH fuse links gG class with high breaking capacity, for use as general protection against overloads and short circuits, intended as protection for cable, power lines and equipment with rated voltage up to 500V.

● STANDARDS:

IEC60269, VDE0636, DIN43620

● SPECIFICATIONS

Frequency Range: 50Hz

Rated voltage: Up to 660V

Rated current: Up to 630A

Protection range: gG/gL

Rated breaking capacity: Up to 120KA

Ref.	Description	Rated Current(A)	Rated Voltage(V)	Breaking Capacity(KA)	Case qty.	Order No.
NH00C	NH00C-4A	4	500	120	200	510004
	NH00C-6A	6	500	120	200	510006
	NH00C-10A	10	500	120	200	510010
	NH00C-16A	16	500	120	200	510016
	NH00C-20A	20	500	120	200	510020
	NH00C-25A	25	500	120	200	510025
	NH00C-32A	32	500	120	200	510032
	NH00C-36A	36	500	120	200	510036
	NH00C-40A	40	500	120	200	510040
	NH00C-50A	50	500	120	200	510050
	NH00C-63A	63	500	120	200	510063
	NH00C-80A	80	500	120	200	510080
	NH00C-100A	100	500	120	200	510100
	NH00-6A	6	500/660	120	108	610006
	NH00-10A	10	500/660	120	108	610010
	NH00-16A	16	500/660	120	108	610016
	NH00-20A	20	500/660	120	108	610020
	NH00-25A	25	500/660	120	108	610026
	NH00-32A	32	500/660	120	108	610032
	NH00-36A	36	500/660	120	108	610036
	NH00-40A	40	500/660	120	108	610040
	NH00-50A	50	500/660	120	108	610050
	NH00-63A	63	500/660	120	108	610063
	NH00-80A	80	500/660	120	108	610080
	NH00-100A	100	500/660	120	108	610100
	NH00-125A	125	500/660	120	108	610125
	NH00-160A	160	500/660	120	108	610186



Ref.	Description	Rated Current (A)	Rated Voltage (V)	Breaking Capacity(KA)	Case qty.	Order No.
NH1 	NH1-80A	80	500/660	120	48	810080
	NH1-100A	100	500/660	120	48	810100
	NH1-125A	125	500/660	120	48	810125
	NH1-160A	160	500/660	120	48	810160
	NH1-200A	200	500/660	120	48	810200
	NH1-225A	225	500/660	120	48	810225
	NH1-250A	250	500/660	120	48	810250
NH2 	NH2-125A	125	500/660	120	36	220126
	NH2-160A	160	500/660	120	36	220160
	NH2-200A	200	500/660	120	36	220202
	NH2-224A	224	500/660	120	36	220224
	NH2-250A	250	500/660	120	36	220250
	NH2-300A	300	500/660	120	36	220300
	NH2-315A	315	500/660	120	36	220315
	NH2-355A	355	500/660	120	36	220355
NH3 	NH2-400A	400	500/660	120	36	220400
	NH3-315A	315	500/660	120	24	320315
	NH3-355A	355	500/660	120	24	320355
	NH3-400A	400	500/660	120	24	320400
	NH3-425A	425	500/660	120	24	320524
	NH3-500A	500	500/660	120	24	320500
	NH3-630A	630	500/660	120	24	320630

Description	Suitable Fuse links	Rate Voltage(V)	Case qty.	Order No.
NTB3	NH00C~NH3	1000	50	163000
NTB4	NT00C~NT4	1000	50	



NH SERIES FUSE LINKS AND BASES

Ref.	No.	Type	Rated Voltage	Rated Current	Dimention(mm)					weight(g)
					A	B	C	D	H	
	0201	NH00C	500/660	10~100						138
	0202	NH00	500/660	10~160	78	50.5	15	30	60	201
	0203	NH0	500/660	6~160	125	67	15	30	60	267
	0204	NH1	500/660	32~250	135	68	20	46	58	447
	0205	NH2	500/660	80~400	150	68	30	58	58	727
	0206	Nh3	500/660	160~630	150	68	36	70	80	975

