

Radiation / RF strength Meter

Home > Products > Radiation Monitor > TM-93



Model No.: : TM-93

Product Description

- Gamma radiation dose rate and dose measurement .
- Alert mode indicator
- Bar Graph display :
- Sampling rate:6 seconds per time
- Battery life: approx. 10 hours
- Dimensions :115x60x31mm (LxWxH)
- RF dose rate: histogram
- Audible key tone alarm function
- Data hold
- 5V USB external power supply
- Power :9V alkaline battery
- Weight : approx. 170 g

Q'ty : 1

Inquiry

Enlargement

- 2.4(inch) color TFT LCD
- 4 digits, 2.4 inches color TFT LCD
- Language :English , Traditional Chinese , Simplified Chinese , Japanese , Spanish

Sample rate	1 time /10 seconds or 1 time /40 seconds
Radiation sensor	Geiger- mueller tube
Measurement range	0.05μSv/h ~39.99μSv/h 5.00μRem/h~3999μSv/h
Resolution	0.01μSv/h 0.01μRem/h
Accuracy	±15% cesium-137
Gamma energy range	10KeV to 1.25MeV
X-rays energy range	3KeV to 3.0MeV
β-beta energy range	25KeV to 3.5MeV
CPM	0~1999
CPS	0~212
Dose logger interval	1 to 999 days

Sample rate	1 time /10 seconds
RF sensor	Single axis sensor
Measurement range	0.1~14.0 V/m
Accuracy	±2dB to 2.45GHz
Frequency range	50MHz to 3.5GHz
Range	0.02μW/m² to 484.6μW/m² 0.01μW/cm² to 45.3μW/cm² 36.1mV/m to 13.90V/m 0.01mA/m to 30.01 mA/m -46 dBm to 16 dBm
Resolution	0.01μW/m²,0.01μW/cm² 0.2 mV/m,0.02 mA/m,2dB

