

Quality and reliability is our tradition KYORITSU

DC mA

MEM

HOLD

-Ò

Φ6

Bluetooth

OUT PUT

AUTO POWER

OFF

DC MILLIAMP CLAMP LOGGER KEW 2510

<u> ()</u> 42 Vpk MAX =

DC ± 120mA MAX

DC 4-20mA Clamp Sensor

Measures DC4-20mA signals without breaking the loop "Advanced models with recording function!"





NEW

- Measures 4 to 20 mA instrumentation and process signals without breaking the loop
- Memory function stores up to 192000 data useful for monitoring the signals over time and fault finding
- Transfer data to PC via Bluetooth

- Top class measurement 0.2% accuracy
- Ø6mm clamp jaw easy to use in tight places
- LED light for illuminating the measurement spot
- Analog output terminal to allow the connection to a recorder or a digital multimeter

KYORITSU ELECTRICAL INSTRUMENTS WORKS, LTD. http://www.kew-ltd.co.jp

KEW 2510 Specifications

REW 2510 Specifications		
DC mA	20/100mA(Auto ranging) ±0.2%rdg±5dgt(0.00mA - 21.49mA) ±1.0%rdg±5dgt(21.0mA - 120.0mA)	
Conductor size	¢6mm max.	
Analog output	Recorder: DC1000mV against DC100mA	
Communication Interface	Bluetooth Ver2.1+EDR Class2	
Applicable Standards	IEC 61010-1, Pollution degree 2 IEC 61010-2-032, IEC 61326-1(EMC) IEC 60529 IP40, EN50581(RoHS)	
Operating temperature & humidity	-10 - +50°C <85%	
Storage temperature & humidity	-20 - +60°C <85%	
Power source	R6/LR6(AA) (1.5V) x4 (Alkaline LR6 is recommended.) External supply (AC adapter MODEL8320)	
Battery life	Approx. 50 hours continuous with alkaline batteries (with Backlight, LED light and Bluetooth feature OFF)	
Dimensions	111(L)x61(W)x46(D)mm : Display unit 104(L)x33(W)x20(D)mm : Sensor 700mm : Sensor Cable	
Weight	Approx. 310g(including batteries)	
Accessories	8320(AC adapter), KEW Windows for 2510(Software) 9096(Carrying case), LR6(AA)x4, Instruction manual Software installation manual	
Optional	7256(Output cord)	



Note: The Auto-power OFF can be disabled for long recording

Please read the "Safety Warnings" in the instruction manual supplied with the instrument thoroughly and completely Safety Warnings : for correct use. Failure to follow the safety rules can cause fire, trouble, electrical shock, etc. Therefore, make sure to operate the instrument on a correct power supply and voltage rating marked on each instrument.

For inquires or orders :







Included Accessories



Optional Accessory



KEW windows for 2510 Carrying case

Selection Guide

	2500	2510 NEW
DC A 20/100mA	~	✓
Conductor size ϕ 6mm max	1	✓
Analog output	1	✓
Memory		✓
Data transmission (Bluetooth)		✓
Power: Battery	~	✓
Power: External Supply		✓



KYORITSU ELECTRICAL INSTRUMENTS WORKS, LTD.

No.5-20, Nakane 2-chome, Meguro-ku, Tokyo, 152-0031 Japan Phone:81-3-3723-0131 Fax:81-3-3723-0152 E-mail:info@kew-ltd.co.jp Factory: Ehime, Japan

http://www.kew-ltd.co.jp

